

hatch skin install

First .. you'll have to disconnect the harness and pass it through the bottom of the 1/4 panel , then you can unbolt the gate .. be sure to presoak the bolts with penetrating fluid .



Once the door is off and on a stable work surface , you can begin to remove the outer



skin with a grinder . The 3 edges L & R sides and lower edge can be ground



off .. just until the seam "pops" . work your way on all 3 corners , and



then on the top you'll need to drill a spot weld . finally , un-doing



the electrical plug , the skin can be removed . The new fiberglass skin is



ready for install laying the new skin in place (to check fitment)



Depending on the bonding product you choose , and we recommend *3M panel bonder #

08115 , you'll want to scuff the panel



and drill holes and cutouts before

installation .. once that is done , your ready to glue



, let dry according to

instructions , and install



Paint , and your done.

Contact Information

Telephone

250-493-9473 available until 5PM PST (west coast)

Shop Hours

8:30AM -3:00PM Mon-Fri. PST (west coast)

Address

Precision 4X4 Center
#109-1280 Commercial Way
Penticton B.C. Canada
V2A 3H5

Electronic mail

General Information: info@toyotafiberglass.com

Customer Support: support@toyotafiberglass.com

Sales: sales@toyotafiberglass.com

Corey CJ@toyotafiberglass.com